



# NAMI<sup>®</sup>

## MANUAL STACKER with Fixed Fork

1. Effortless lifting at an economical price.
2. This lifting is designed to handle skids, position work feed machinery, and other handling tasks.
3. Units in-operated by hydraulic foot pump together with handle, marking lifting effortless, also foot pedal or handle lowering valve.
4. Hydraulic cylinder with chrome-plated ram, also master fitted with heavy-duty roller bearings with flow control valve located at base of lift cylinder that regulated lowering speed for safety.
5. Steer with rear swivel casters for raising maneuvering speed for safety.
6. Wheel brake is standard.
7. Roller chain with over 5 times capacity yield.

Model		MSE 500			MSE1000			MSE 1500		
Capacity	kg	500			1000			1500		
Lifting height	mm	1600	2500	3000	1600	2500	3000	1600	2500	3000
Load Center	mm	600			600			600		
Overall truck width*length	mm	560*1150			560*1150			560*1150		
Turning radius	mm	1540	1550	1590	1600	1590	1600	1590	1600	
Lifting speed	(mm/time)	> 20			> 16			> 12		
Overall length	mm	1650	1650	1650	1650	1650	1650	1650	1650	1650
Overall width	mm	630	680	680	680	760	760	690	760	760
Overall height	mm	1970	1770	2020	2020	1770	2020	2070	1770	2020
Selfweight	kg	150	230	256	188	276	297	246	330	360
Steering wheel	mm	Ø 150			Ø 150			Ø 150		
Front wheel	mm	Ø 80			Ø 80			Ø 80		



## MANUAL STACKER with Adjustable Fork



1. Effortless lifting at an economical price.
2. This lifting is designed to handle skids, position work feed machinery, and other handling tasks.
3. Units in-operated by hydraulic foot pump together with handle, marking lifting effortless, also foot pedal or handle lowering valve.
4. Hydraulic cylinder with chrome-plated ram, also master fitted with heavy-duty roller bearings with flow control valve located at base of lift cylinder that regulated lowering speed for safety.
5. Steer with rear swivel casters for raising maneuvering speed for safety.
6. Wheel brake is standard.
7. Roller chain with over 5 times capacity yield.

Model		MSA1000			MSE 1500			
Capacity	kg	1000			1500			
Lifting height	mm	1600	2500	3000	1600	2500	3000	
Load Center	mm	400			400			
Fork Length	mm	915			915			
Turning radius	mm	1650			1650			
Outside width between legs	mm	1080-1360			1080-1360			
Inside width between legs	mm	960-1240			960-1240			
Outside width between forks	mm	210-800			230-800			
Inside width between forks	mm	10-600			10-580			
Lifting speed	(mm/time)	≥ 16			≥ 12			
Overall dimension	Length	mm	1480			1480		
	Width	mm	1080-1360			1080-1360		
	Height	mm	2020	1700	2020	2020	1700	2020
Wheel	Front Wheel Diameter	mm	80			80		
	Rear Wheel Diameter	mm	150			150		
Self Weight	kg	270	358	378	282	376	387	